

JC849 U.S. PTO
07/27/00

07-28-00

JC857 U.S. PTO
09/626981
07/27/00

A

Please type a plus sign (+) inside this box → ☒

Approved for use through 09/30/2000. OMB 0651-0032
Patent and Trademark Office: U.S. DEPARTMENT OF COMMERCE
PTO/SB/05 (4/98)

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number.

UTILITY PATENT APPLICATION TRANSMITTAL (Only for new nonprovisional applications under 37 C.F.R. § 1.53(b))	Attorney Docket No.	13DV13683
	First Inventor or Application Identifier	DOUGLAS M. CARPER
	Title	FIBER REINFORCED COMPOSITE ARTICLE,
	Express Mail Label No.	EL627655048US

APPLICATION ELEMENTS See MPEP chapter 600 concerning utility patent application contents.	ADDRESS TO: Assistant Commissioner for Patents Box Patent Application Washington, DC 20231
1. <input checked="" type="checkbox"/> * Fee Transmittal Form (e.g., PTO/SB/17) (Submit an original and a duplicate for fee processing)	5. <input type="checkbox"/> Microfiche Computer Program (Appendix)
2. <input checked="" type="checkbox"/> Specification [Total Pages 16] (preferred arrangement set forth below) <ul style="list-style-type: none">- Descriptive title of the invention- Cross References to Related Applications- Statement Regarding Fed sponsored R & D- Reference to Microfiche Appendix- Background of the invention- Brief Summary of the invention- Brief Description of the Drawings (if filed)- Detailed Description- Claim(s)- Abstract of the Disclosure	6. Nucleotide and/or Amino Acid Sequence Submission (if applicable, all necessary) <ul style="list-style-type: none">a. <input type="checkbox"/> Computer Readable Copyb. <input type="checkbox"/> Paper Copy (identical to computer copy)c. <input type="checkbox"/> Statement verifying identity of above copies
3. <input checked="" type="checkbox"/> Drawing(s) (35 U.S.C. 113) [Total Sheets 2]	ACCOMPANYING APPLICATION PARTS
4. Oath or Declaration [Total Pages <input]<ul="" type="checkbox"/> a. <input type="checkbox"/> Newly executed (original or copy) b. <input type="checkbox"/> Copy from a prior application (37 C.F.R. § 1.63(d)) (for continuation/divisional with Box 16 completed)<ul style="list-style-type: none">i. <input type="checkbox"/> DELETION OF INVENTOR(S) Signed statement attached deleting inventor(s) named in the prior application, see 37 C.F.R. §§ 1.63(d)(2) and 1.33(b).	7. <input checked="" type="checkbox"/> Assignment Papers (cover sheet & document(s))
* NOTE FOR ITEMS 1 & 13: IN ORDER TO BE ENTITLED TO PAY SMALL ENTITY FEES, A SMALL ENTITY STATEMENT IS REQUIRED (37 C.F.R. § 1.27), EXCEPT IF ONE FILED IN A PRIOR APPLICATION IS RELIED UPON (37 C.F.R. § 1.28).	
8. <input type="checkbox"/> 37 C.F.R. § 3.73(b) Statement (when there is an assignee) <input checked="" type="checkbox"/> Power of Attorney	
9. <input type="checkbox"/> English Translation Document (if applicable)	
10. <input checked="" type="checkbox"/> Information Disclosure Statement (IDS)/PTO-1449 5 Copies of IDS Citations	
11. <input type="checkbox"/> Preliminary Amendment	
12. <input type="checkbox"/> Return Receipt Postcard (MPEP 503) (Should be specifically itemized)	
13. <input type="checkbox"/> * Small Entity Statement(s) <input type="checkbox"/> Statement filed in prior application, Status still proper and desired (PTO/SB/09-12)	
14. <input type="checkbox"/> Certified Copy of Priority Document(s) (if foreign priority is claimed)	
15. <input type="checkbox"/> Other: _____	

16. If a CONTINUING APPLICATION, check appropriate box, and supply the requisite information below and in a preliminary amendment:
☐ Continuation ☐ Divisional ☐ Continuation-in-part (CIP) of prior application No: _____
Prior application information: Examiner _____ Group / Art Unit: _____

For CONTINUATION or DIVISIONAL APPS only: The entire disclosure of the prior application, from which an oath or declaration is supplied under Box 4b, is considered a part of the disclosure of the accompanying continuation or divisional application and is hereby incorporated by reference. The incorporation can only be relied upon when a portion has been inadvertently omitted from the submitted application parts.

17. COMMUNICATIONS ADDRESS	
XXX Customer Number or Bar Code Label	(Insert Customer Number of each bar code label here) 6111
Name	PATENT TRADEMARK OFFICE
Address	
City	State Zip Code
Country	Telephone Fax

Name (Print/Type)	RODNEY M. YOUNG	Registration No. (Attorney/Agent)	40,882
Signature	<i>Rodney Young</i>	Date	7/27/00

Burden Hour Statement: This form is estimated to take 0.24 hours to complete. Time will vary depending upon the needs of the individual case. Any comments on the amount of time you are required to complete this form should be sent to the Chief Information Officer, Patent and Trademark Office, Washington, DC 20231. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. SEND TO: Assistant Commissioner for Patents, Box Patent Application, Washington, DC 20231.

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

Applicants:	DOUGLAS MELTON CARPER	:	
		:	
Serial No.:		:	
		:	Group Art Unit:
		:	
Filed:	FILED HEREWITH	:	Examiner: Not
		:	Known
For:	FIBER REINFORCED	:	
	COMPOSITE ARTICLE, FIBER	:	
	MEMBER, AND METHOD FOR	:	
	MAKING	:	

PRELIMINARY AMENDMENT

Assistant Commissioner for Patents
Washington, D.C. 20231

Dear Sir:

In the Claims

Please amend claims 13, 19, and 27 as follows:

In Claim 13, at line 1, please delete the words “, for making the fiber reinforced composite article of claim 1,”.

In Claim 19, at line 1, please delete the first occurrence of the word “the” and insert therefor, the word - - a - - ; and also in Claim 19, at lines 1-2, please delete the words “of claim 1” and insert therefor, the word - - comprising - - .


In Claim 27, at line 1, please delete the first occurrence of the word “the” and insert therefor, the word - - a - - ; and also in Claim 27 at line 1, delete the words “of claim 13” and insert therefor, the word - - comprising - - .

002229-072950

REMARKS

This amendment to Claims 13, 19, and 27 is to more particularly point out and to distinctly claim the subject matter of Applicants' invention. These changes involve minor typographical and proofing errors in order to clarify these as independent claims. No new matter has been added. Applicant respectfully requests an action on the merits.

Respectfully submitted,



**Rodney M. Young
Reg. No. 40,882
(513) 243-9835**

**July 27, 2000
General Electric Company
One Neumann Way, M/D H17
Cincinnati, OH 45215-6301**

004240-00000000

FIBER REINFORCED COMPOSITE ARTICLE, FIBER MEMBER, AND
METHOD FOR MAKING

BACKGROUND OF THE INVENTION

5 This invention relates to a member comprising fibers, to a composite article reinforced with fibers, and to a method for making such member and article. More particularly, in one form, it relates to a fiber reinforced composite article that, during service operation, experiences concurrently a plurality of temperatures and stresses varying between a plurality of regions of the article.

10 In power generation apparatus, for example a gas turbine engine, wide variations in operating temperatures are experienced from inlet to exhaust, as well as across or within individual components of such an engine. An example of such thermal variation has been observed within the engine exhaust system across or within regions of panels such as exhaust flaps. Another example is a turbine engine blading component, such as a blade, vane, strut, etc., having a surface or skin region that
15 experiences a temperature greater than does reinforcing or strengthening spars in the component.

Such high thermal gradients across or within such an article or component or within a region, sometimes called a hot spot, of the article has generated relatively high thermal strains sufficient to limit the operating capability of the article. For
20 example, cooler edge regions of a gas turbine engine exhaust flap, made of a high temperature oxide fiber reinforced ceramic matrix composite material, existing concurrently with a higher temperature region within or away from the edge regions, have been observed to develop cracks that can decrease the operating life of the article. Such degradation is believed to result from the inability of the reinforced
25 structure of an article, made generally from a single kind of material, to compensate for different stress levels developed from a stress conflict between different temperature regions. The reinforced matrix of the composite including reinforcing fibers, for example of a single kind, alone does not have the capability to withstand or

EXPRESS #
EL 627655048 US - JULY 27, 2000

compensate for such wide strain variations across the operating temperature range of the article.

BRIEF SUMMARY OF THE INVENTION

5 The present invention, in one form, provides a fiber reinforced composite article comprising a matrix and reinforcing fibers. During operation, the article experiences concurrently in the article a plurality of operating temperatures varying between a plurality of regions of the article. For example, operating temperatures can vary within a total temperature range of about 900 - 2000° F. In one form of operation, a first region of the article experiences a first temperature, for example of about 1800° F in the range of about 1600 - 2000° F, that develops a first stress in that first region of the article. Concurrently in operation with the first region, a second region of the article experiences a second temperature less than the first temperature, for example of about 1100° F in the range of about 900 - 1300° F, that develops a second stress in that second region of the article greater than the first stress. Such difference in stress between regions of a fiber reinforced composite article has been observed to result in cracking in higher stressed, lower temperature region, for example at an edge portion of an article.

20 A form of the present invention provides, for a plurality of regions of an article, strength levels of reinforcing fibers adequate to compensate for the operating stress level in its respective region. The fibers appropriately are selected for each region in making an article or a reinforcing member, to provide a strength level greater than the respective stress experienced at operating temperature in that region. In part, as will be described below, such strength levels are based on use of fibers in a matrix having different coefficients of thermal expansion (CTE), sometimes referred to as " α ", determined at the intended operating temperature. In one form, the selection of fibers to provide appropriate strength levels in the regions is based on a difference in thermal stress levels from the product of the following for each region: a ratio of each respective area of a region to the total area of an article portion, the elastic modulus of the fiber reinforced matrix, the CTE of such reinforced matrix, and the temperature at which each region operates. In that form of the invention, such

product of the first, relatively hotter, region is less than such product for the second, relatively cooler region. One form of such a relationship, to be referred to hereinafter as the "relationship", is $A_1 E_1 \alpha_1 T_1 - A_2 E_2 \alpha_2 T_2 < S_2$, in which, as identified above, respectively for the regions 1 and 2, A is the area ratio of a region to a total area of the regions, E is the elastic modulus of the fiber reinforced matrix, α is the CTE of the fiber reinforced matrix at the operating temperature in °F, T is the operating temperature in °F, and S is the strength of a relatively cooler region. In this example, the second region, region 2, has a second strength greater than the first strength in the first region.

Another form of the invention is a member in the form of a mixture of such first and second fibers, for example as a fabric, weave, braid, lay-up, etc., used to make a fiber reinforced composite article. Still other forms are methods of making such a member or making such an article, comprising selecting the first and second fibers and their relative mixture and location in the member or article as a function of their intended operating conditions.

BRIEF DESCRIPTION OF THE DRAWINGS

Figure 1 is a diagrammatic view of a panel representing one form of article provided according to the present invention, in which operating temperature varies from a region within the panel outwardly toward the panel edge regions.

Figure 2 is a diagrammatic view of a panel representing another form of the present invention, in which operating temperature varies substantially from a first end region to a second end region.

Figure 3 is a comparison of variation in coefficient of thermal expansion across a range of temperatures for two different fiber reinforced matrix composite systems.

Figure 4 is a diagrammatic view of a member in still another form of the present invention: in the form of woven fabric comprising, in selected areas, a single

or a mixture of first and second fibers, according to the present invention, for use in making a fiber reinforced composite article.

DETAILED DESCRIPTION OF THE INVENTION

5 Currently, one form of gas turbine engine exhaust flap, conveniently represented generally in the form of a panel, is made of a ceramic matrix reinforced generally uniformly throughout with a single kind of high temperature oxide fiber. One form of such an exhaust flap includes an aluminosilicate matrix, made from commercially available SM8 sub-micron alumina powder and silica. The matrix is reinforced with an oxide fiber nominally comprising, by weight, 85% alumina and
10 15% silica, and commercially available as Nextel 720 roving material. During one type of service operation, the exhaust flap experienced a first temperature ranging from about 1600 - 2000° F in at least one region away from peripheral edge regions, within the panel, to a second temperature less than the first temperature and in the range of about 900 - 1300° F at peripheral regions of the flap. It was observed that
15 such temperature variation in the flap caused cracking at peripheral edges resulting from excessive strain of the composite at such cooler points, while maintaining the integrity of the structure in the hotter region.

One diagrammatic embodiment of a panel intended to experience the type of service operation described above is shown in the diagrammatic view of Figure 1.
20 The panel shown generally at 10 represents, diagrammatically, an article such as a gas turbine engine exhaust flap. During service operation of the panel, the at least one first region 12, away from peripheral edge or second region 14 is shown to be generally discrete from edge region 14 within the panel. First region 12 experiences a first temperature greater than a second temperature experienced by edge region 14.

25 One form of the present invention avoids generation of excessive, destructive strain in the panel by disposing in each of the first and second regions 12 and 14 different high temperature reinforcing fibers, or a mixture or blend of a plurality of high temperature reinforcing fibers. Each fiber or mixture of fibers has a different coefficient of expansion (CTE) at the temperature at which it operates, to provide,

with the matrix, the above described "relationship". Each of the different fibers in the respective regions, or the mixture or blend, is tailored or selected between regions to provide in a region a strength level adequate to resist in the article the generation of excessive strain sufficient to cause degradation in the article structure across the entire operating temperature range. That embodiment of the invention uses, in a cooler region, a single kind of fiber or a mixture of fibers having, in the single kind of fiber or in the mixture of fibers, relatively high thermal expansion characteristics to yield appropriately higher thermal strain. Concurrently, that embodiment uses, in a relatively hotter region, fibers having, in the single kind of fiber or in the mixture of fibers, a relatively lower thermal expansion characteristic. The result, through the "relationship", is reduction in thermal strain, including, in some forms, resistance to biaxial thermal strains, in the cooler region that previously has resulted in cracking from excessive thermal strain. Examples of high temperature fibers used in forms of the present invention include, but are not limited to, at least one or a combination of alumina, silica, glass, graphite, carbon, carbides, tungsten, and boron.

Another diagrammatic embodiment of a panel 10, intended to experience concurrently a plurality of temperatures in regions of the article during operation, is shown in the diagrammatic view of Figure 2. In that embodiment, a first end region 16 experiences a first temperature greater than a second end region 18, spaced apart from first end region 16.

One embodiment of the present invention for reinforcing an alumina matrix used two kinds of fibers based on alumina in the "relationship". A first of the plurality of fibers, in a method for making a reinforcing member for use in making a fiber reinforced matrix composite article, selected predominantly for a first, higher temperature region of about 1650° F, representative of the range of about 1600 - 2000° F, had a first CTE of about 3.37×10^{-6} / °F at that temperature of 1650° F. In this example, the first fiber predominantly for the higher temperature was the above described Nextel 720 ceramic fiber roving. A second of the plurality of fibers in this embodiment, used alone or in combination with other fibers for a second, lower or cooler temperature region of about 1100° F, representative of the range of about 900 - 1300° F, was a commercially available fiber Nextel 610 ceramic roving substantially

of alumina, with a second CTE of about $3.93 \times 10^{-6} / ^\circ\text{F}$ at the second temperature, and greater than the first CTE at the first temperature.

The above-identified fibers were used in making one series of article specimens for evaluation of fiber reinforced ceramic matrix composite forms of the present invention. The matrix was an ultra pure, sub-micron size ceramic of substantially pure alumina, marketed by Baikowski International Corporation as SM8 material, mixed in a silica binder provided by the thermal decomposition of a polymer including silicon. The matrix comprised, by weight, about 80% alumina and about 20% silica. The specimens were woven fabric reinforced composites including various single or hybrid reinforcing mixtures of the above-identified Nextel 720, (identified below as "N7") and Nextel 610, (identified below as "N6") ceramic rovings. In this specific series of evaluations, the following values of the above-described "relationship" were used for the specimens:

$$A_1 = 0.66; A_2 = 0.33$$

$$T_1 = 1650^\circ \text{F}; T_2 = 1100^\circ \text{F}$$

$$E_{N7}: @ T_1 = 11 \times 10^6; @ T_2 = 10.4 \times 10^6$$

$$E_{N6}: @ T_1 = 12 \times 10^6; @ T_2 = 11.8 \times 10^6$$

$$\alpha_{N7}: @ T_1 = 3.37 \times 10^{-6}; @ T_2 = 3.03 \times 10^{-6}$$

$$\alpha_{N6}: @ T_1 = 4.45 \times 10^{-6}; @ T_2 = 3.93 \times 10^{-6}$$

$$S_{N7} @ T_2 = 21000 \text{ pounds per square inch (psi)}$$

$$S_{N6} @ T_2 = 35000 \text{ psi}$$

In one example, an article specimen had all Nextel 720 rovings as the reinforcing fiber. Using the above values, the difference of the two products in the "relationship" calculated to be a stress of about 28,900 psi. Because the stress value 28,900 psi is greater than the strength of about 21,000 psi of Nextel 720 material in the region at 1100°F , the region of such a fiber reinforced composite article at about 1100°F can degrade and crack from the excessive stress.

In another example, an article specimen had all Nextel 610 rovings as the reinforcing fiber. Using the above values, the difference of the two products in the

“relationship” calculated to be a stress of about 41,300 psi. Because the stress value 41,300 psi is greater than the strength of about 35,000 psi of Nextel 610 material in the region at about 1100° F, the region of such a fiber reinforced composite article at about 1100° F can degrade and crack from excessive stress.

5 In still another example, this one according to a form of the present invention, an article specimen had all Nextel 720 rovings in the hotter region 1 at 1650° F and all Nextel 610 rovings in the cooler region 2 at 1100° F. Using the above values, the difference in the two products of the “relationship” calculated to be a stress of about 23,500 psi. Because the operating stress value 23,500 psi is less than the strength of
10 about 35,000 psi in the region at 1100° F, the strength of the fiber in that region would exceed the operating stress. Therefore according to a form of the present invention, degradation or cracking in that region of an article would not occur, while the integrity of the hotter region at 1650° F would be maintained using Nextel 720 rovings in that hotter region.

15 Figure 3 is a graphical comparison of coefficients of thermal expansion at different temperatures of the above-identified Nextel 610 and Nextel 720 alumina-based ceramic rovings in an alumina-based matrix including silica, of the type described above. The data in Figure 3 for those two types of fiber reinforced matrix composites represent the type of data that can be used in connection with the present
20 invention in the “relationship” to select the type and amounts of fibers for the plurality of regions of an article, operating at different temperatures.

As can be appreciated, mixtures or blends of fibers concurrently for different regions of an article can be selected to be of a single type, and/or of various mixtures or blends as are appropriate to provide, according to embodiments of the present
25 invention, the strength in a region greater than that region’s operating stress. In one preferred embodiment of the present invention for a high temperature gas turbine engine component, fibers are selected for or included in a region of a matrix in the range of about 20 – 70% by volume. At least about 20 vol. % fiber is required to provide adequate reinforcement. A composite with greater than about 70 vol. % fiber
30 includes insufficient matrix for the integrity of the composite.

One example of a member for fiber reinforcement provided in accordance with a form of the present invention and having concurrently a plurality of different combinations of fibers is shown in the diagrammatic view of Figure 4. The member, shown diagrammatically generally at 20 in Figure 4, is a woven fabric including various regions of fiber combinations for use as fiber reinforcement in a fiber reinforced composite article. In one form of manufacture of a fiber reinforced matrix composite article, a plurality of members 20 are disposed in a stack, for example maintaining the same relative position shown in Figure 4, as the fiber reinforcement for a matrix.

Member 20, representing different combinations of fibers that can be selected, and if necessary combined, appropriately for intended operating conditions, was woven with different fiber combinations, in a pattern repeated in the fabric. Then the fabric was cut in desired shapes for stacking. Regions 22, representing a hottest operating region of a member, included all Nextel 720 rovings in both the warp and fill directions. Regions 24, representing a coolest operating region of a member, included all Nextel 610 rovings in both the warp and fill directions. Regions 26 and 28 represented regions with operating temperatures between those of regions 22 and 24. Region 26 included all Nextel 720 rovings in the warp direction and all Nextel 610 rovings in the fill direction. Region 28 included all Nextel 610 rovings in the warp direction and all Nextel 720 rovings in the fill direction. A plurality of this embodiment of a member of the present invention was arranged in a stack to provide the fiber reinforcement for a fiber reinforced alumina matrix composite. The composite included about 45 vol. % fibers, with the balance essentially alumina matrix, within the preferred range of about 20 – 70 vol. % fibers.

The present invention has been described, in various general embodiments and forms, in connection with specific examples and combinations. However, it should be understood that these are intended to be typical of rather than in any way limiting on the scope of the present invention. Those skilled in the various arts associated with this invention will understand that it is capable of variations, combinations and modifications without departing from the scope of the appended claims.

WHAT IS CLAIMED IS:

1. A fiber reinforced composite article comprising a matrix and reinforcing fibers, the article during operation experiencing concurrently in the article a plurality of operating temperatures and stresses, varying between a plurality of regions of the article;

a first region of the article during operation experiencing a first temperature and a first stress, and including first fibers having a first strength greater than the first stress; and,

a second region of the article during operation experiencing a second temperature less than the first temperature and a second stress greater than the first stress, and including second fibers having a second strength greater than the second stress.

2. The article of claim 1 in which:

the first fibers have a first coefficient of thermal expansion (CTE) at the first temperature; and,

the second fibers have a second CTE at the second temperature greater than the first CTE at the first temperature.

3. The article of claim 2 in which the second strength of the second region is greater than the difference between the first stress and the second stress as determined by the relationship:

$A_1 E_1 \alpha_1 T_1 - A_2 E_2 \alpha_2 T_2 < S_2$, in which, respectively for the first region (1) and the second region (2):

A is the area ratio of a region area to a total area of the regions,

E is the elastic modulus of the fiber reinforced matrix,

α is the CTE of the fiber reinforced matrix at the operating temperature in °F,

T is the operating temperature in °F, and

S is the strength of the second region.

4. The article of claim 3 in which the first and second fibers are in at least one form selected from the group consisting of fabric, weave, braid, and lay-up.

5. The article of claim 3 in which:

the first temperature is in the range of about 1600 - 2000° F; and,

5 the second temperature is in the range of about 900 - 1300° F.

6. The article of claim 5 in which the matrix is ceramic based on alumina.

7. The article of claim 5 in which the fibers are included in the range of about 20 - 70 volume %.

8. The article of claim 6 in which the first and second fibers are based on alumina.

9. The article of claim 6 in which the matrix includes silica.

10. The article of claim 5 in the form of a turbine engine article in which:
the matrix is a ceramic; and,

15 the first fibers and the second fibers are high temperature fibers made from at least one material selected from the group consisting of alumina, silica, glass, graphite, carbon, carbides, tungsten, boron, and their mixtures.

11. The article of claim 9 in the form of a gas turbine engine exhaust flap in which the fibers are included in each region in the range of about 20 - 70 volume %.

12. The article of claim 4 in the form of a gas turbine engine blading component in which the fibers are included in each region in the range of about 20 - 70 volume %.

13. A member, for making the fiber reinforced composite article of claim 1, comprising reinforcing fibers for reinforcement of a fiber reinforced composite article, the member during operation experiencing concurrently in the member a plurality of operating temperatures and stresses, varying between a plurality of regions of the member;

a first region of the member during operation experiencing a first temperature and a first stress, and including first fibers having a first strength greater than the first stress; and,

5 a second region of the member during operation experiencing a second temperature less than the first temperature and a second stress greater than the first stress, and including second fibers having a second strength greater than the second stress.

14. The member of claim 13 in which:

10 the first fibers have a first coefficient of thermal expansion (CTE) at the first temperature; and,

the second fibers have a second CTE at the second temperature greater than the first CTE at the first temperature.

15 15. The member of claim 14 in which the second strength of the second region of the article is greater than the difference between the first stress and the second stress as determined by the relationship:

$A_1 E_1 \alpha_1 T_1 - A_2 E_2 \alpha_2 T_2 < S_2$, in which, respectively for the first region (1) and the second region (2):

A is the area ratio of a region area to a total area of the regions,

E is the elastic modulus of the fiber reinforced matrix,

20 α is the CTE of the fiber reinforced matrix at the operating temperature in °F,

T is the operating temperature in °F, and

S is the strength of the second region.

25 16. The member of claim 14 in at least one form selected from the group consisting of fabric, weave, braid, and lay-up.

17. The member of claim 15 in which:

the first temperature is in the range of about 1600 - 2000° F; and,

the second temperature is in the range of about 900 - 1300° F.

18. The member of claim 17 in which the first and second fibers are based on alumina.

19. In a method for making the fiber reinforced matrix composite article of claim 1, the steps of:

5 selecting the first fibers to have the first strength greater than the first stress;
 selecting the second fibers to have the second strength greater than the second stress;

 disposing the first fibers as reinforcing fibers in the matrix in the first region of the article; and,

10 disposing the second fibers as reinforcing fibers in the matrix in the second region of the article.

20. The method of claim 19 in which:

 the first fibers have a first coefficient of thermal expansion (CTE) at the first temperature; and,

15 the second fibers have a second CTE at the second temperature greater than the first CTE at the first temperature.

21. The method of claim 20 in which the second strength of the second region is greater than the difference between the first stress and the second stress and is determined by the relationship:

20 $A_1 E_1 \alpha_1 T_1 - A_2 E_2 \alpha_2 T_2 < S_2$, in which, respectively for the first region (1) and the second region (2):

 A is the area ratio of a region area to a total area of the region,

 E is the elastic modulus of the fiber reinforced matrix,

α is the CTE of the fiber reinforced matrix at the operating temperature

25 in °F,

 T is the operating temperature in °F, and

 S is the strength of the second region.

22. The method of claim 20 in which the first and second fibers are provided in at least one form selected from the group consisting of fabric, weave, braid, and lay-up for disposing in the first and second regions.

23. The method of claim 22 in which the first fibers and the second fibers are high temperature fibers are made from at least one material selected from the group consisting of alumina, silica, glass, graphite, carbon, carbides, tungsten boron and their mixtures.

24. The method of claim 22 for making a turbine engine fiber reinforced composite article in which:
the matrix of the composite article is based on alumina; and,
the first fibers and the second fibers are disposed in the matrix in the range of about 20 – 70 volume %.

25. The method of claim 24 in which:
the composite article is a gas turbine engine exhaust flap;
the first temperature is in the range of about 1600 - 2000° F;
the second temperature is in the range of about 900 - 1300° F; and,
the first and second fibers are based on alumina.

26. The method of claim 21 in which:
the composite article is a gas turbine engine blading component; and,
the first fibers and the second fibers are disposed in the matrix in the range of about 20 – 70 volume %.

27. In a method for making the member of claim 13, the steps of:
selecting the first fibers to have the first strength greater than the first stress;
selecting the second fibers to have the second strength greater than the second stress;
disposing the first fibers as reinforcing fibers in the matrix in the first region of the member; and,
disposing the second fibers as reinforcing fibers in the matrix in the second region of the member.

the first fibers have a first coefficient of thermal expansion (CTE) at the first temperature; and,

5

10

10

in °F,

S is the strength of the second region.

20

20

25

the second temperature is in the range of about 900 - 1300° F; and,



5

the composite article is a gas turbine engine exhaust flap; and,

34. The method of claim 28 for making a member for use as a fiber reinforcement in a fiber reinforced gas turbine engine blading component in which the first fibers and the second fibers are disposed in the matrix in the range of about 20 – 70 volume %.

5

10



<u>24</u>	<u>26</u>	<u>24</u>
<u>28</u>	<u>22</u>	<u>28</u>
<u>24</u>	<u>26</u>	<u>24</u>

COEFFICIENT OF THERMAL EXPANSION
FOR THE REINFORCED MATRIX COMPOSITE




FIG. 3

**DECLARATION AND POWER OF ATTORNEY
FOR PATENT APPLICATION**

Docket Number
13DV13683

As a below named inventor, I hereby declare that:

My residence, post office address, and citizenship are as stated below next to my name.

I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled:

-----FIBER REINFORCED COMPOSITE ARTICLE, FIBER MEMBER, AND METHOD FOR MAKING-----

the specification of which

☒ is attached hereto
OR

☐ was filed on _____ as United States Application Number or PCT International Application Number _____
and was amended on _____ (if applicable).

I hereby state that I have reviewed and understand the contents of the above identified specification, including the claims, as amended by any amendment specifically referred to above.

I acknowledge the duty to disclose information which is material to patentability as defined in Title 37 Code of Federal Regulations, §1.56.

I hereby claim foreign priority benefits under Title 35, United States Code §119 (a)-(d) or §365 (b) of any foreign application(s) for patent or inventor's certificate, or §365 (a) of any PCT international application which designated at least one country other than the United States of America, listed below and have also identified below any foreign application for patent or inventor's certificate, or of any PCT international application having a filing date before that of the application on which priority is claimed.

PRIOR FOREIGN APPLICATION(s)

Priority Claimed

☐ Yes ☐ No

☐ Yes ☐ No

_____ (Number)	_____ (Country)	_____ (Day/Month/Year Filed)
_____ (Number)	_____ (Country)	_____ (Day/Month/Year Filed)

☐ Additional foreign application numbers are listed on a supplemental priority data sheet attached hereto.

I hereby claim the benefit under Title 35, United States Code §119 (e) of any United States provisional application(s) listed below.

☐ Additional provisional application numbers are listed on a supplemental priority data sheet attached hereto.

_____ (Application Number)	_____ (Filing Date)
-------------------------------	------------------------

I hereby claim the benefit under Title 35, United States Code §120 of any United States Application(s), or §365 (c) of any PCT international application designating the United States of America, listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States or PCT International application in the manner provided by the first paragraph of Title 35, United States Code §112, I acknowledge the duty to disclose information which is material to patentability as defined in Title 37, Code of Federal Regulations §1.56 which became available between the filing date of the prior application and the national or PCT international filing date of this application.

_____ (Application Number)	_____ (Filing Date)	_____ (Status - patented, pending, abandoned)
_____ (Application Number)	_____ (Filing Date)	_____ (Status - patented, pending, abandoned)

I hereby appoint the registered practitioners associated with Customer Number 006111 to prosecute this application and to transact all business in the Patent and Trademark Office connected therewith.

Address all telephone calls to: RODNEY M. YOUNG at telephone number (513) 243-9835

Address all correspondence to: **GENERAL ELECTRIC COMPANY
ATTN: ANDREW C. HESS
GE AIRCRAFT ENGINES
ONE NEUMANN WAY, M/D H17
CINCINNATI, OH 45215-6301**



I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

SOLE OR FIRST INVENTOR:

Full name: DOUGLAS MELTON CARPER

First Name

Middle Name

Last Name

Signature: Douglas Melton Carper

Date

7/26/00

Residence: BLUE ASH, OHIO

City and State

Citizenship: US

Post Office Address: 4894 HUNT ROAD, #104, BLUE ASH, OH 45242

SECOND JOINT INVENTOR:

Full name:

First Name

Middle Name

Last Name

Signature: _____

Date

Residence: _____

City and State

Citizenship: _____

Post Office Address: _____

THIRD JOINT INVENTOR:

Full name:

First Name

Middle Name

Last Name

Signature: _____

Date

Residence: _____

City and State

Citizenship: _____

Post Office Address: _____

FOURTH JOINT INVENTOR:

Full name:

First Name

Middle Name

Last Name

Signature: _____

Date

Residence: _____

City and State

Citizenship: _____

Post Office Address: _____